

Cerex UV Hound

UV-DOAS Multi-Gas Analyzer

Designed for extremely sensitive, transportable point detection of **individual species** (such as Benzene, Chlorine, Butadiene, Carbon Disulfide, Sulfur Dioxide, Naphthalene, and more)



Features

- Benzene (1.0 ppb) and other gases down to low parts per billion minimum detection limits (gas specific) within seconds; optional sensors for non-UV gases
- Easy to operate, all-in-one package portable by wheels/handles or fixed installation available
- Low cost of ownership, no-maintenance; only 3 consumables: UV lamp, sample & case air filters
- 4 hour internal battery, or up to 14 hour battery life with external batteries; continuous operation on AC power
- Internal optical path length up to 22 meters

- Results available in real-time data output rates from 15 sec. to 5 min
- User-configurable open-source gas library
- Full remote control over network or internet cellular-ready
- Continuous, automated background update no cylinder gases or zero air required to update backgrounds
- Raw spectrographic information in .csv format for instant analysis, compared to "black box" solutions
- No calibration required; can be challenged or QA verified using certified cylinder gases



Cerex Monitoring Solutions places customer service and support as its highest priority and commits to long standing relationships that do not end after the sale of an analyzer.

Side Handle

With over a decade of use by emergency personnel, government agencies, and industry, the UV HOUND is a proven highly dependable analyzer for the accurate and sensitive monitoring of single gases and mixtures.

Cerex's UV HOUND is the most cost effective solution for continuous monitoring of parts per billion levels with real time speciation of BTEX, Ammonia, Nitric Oxide, Nitrogen Dioxide, Sulfur Dioxide, and more gases.

Benzene in particular can be detected down to 1.0 ppb; this capability is one of many reasons why some of the world's largest petrochemical refineries deploy the UV HOUND in their monitoring challenges.

> Touchscreen PC with remote access

Wheels (Underneath)



General Specifications

UV Hound (Standard Model) Analyzer Model

Analyzer Type Portable point multi-gas UV-DOAS

Applications Refinery fence-line monitoring of Benzene, Toluene, and Xylenes (BTEX), Brownfield Remediation,

Chemical Depot Monitoring, Manufactured Gas Plant Remediation (MGP), Perimeter Ambient

Monitoring System (PAMS), Superfund Site Remediation, Tank Farm Monitoring

Minimum Detection Limit Gas-specific, typical parts per billion

Air cooled (optional TE air conditioner) **Instrument Cooling**

Operating Conditions Temperature 0°C to 50°C

Humidity 0 to 100% non-condensing Rain **Direct Exposure Rated Dust/Sand Direct Exposure Rated**

General purpose atmospheres - not rated for HAZLOC zones

Installation Portable or permanent installation within shelter

Interface Integrated touchscreen PC with MS Windows™ 10/11 OS

USB, ethernet ports

